

ASUS BE27ACGN

Docking Monitor



Accessory slot for phone holder

PC mounted via mini PC kit

Key Features



Optimized for the finest image and color quality with 178° wide-viewing-angle



120Hz refresh rate gives you so much more on top of the best smooth and quality for any content



Extensive connectivity of USB-C, HDMI, DP in, DP out for daisy chain, USB hub and earphone jack



DisplayPort allows users to daisy chain for a multi-display setup from one video source.



Embedded USB3.2 hub (4 ports) for connecting mouse, keyboard, or other USB devices



Full function USB-C connection for DisplayPort video, USB data transmission and supports up to 96W power delivery



RJ-45

Delivers stable Internet connection and one-cable docking to your laptop with RJ45 and USB-C connection



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel (+180° ~ -180°), pivot, and height adjustments



Wall Mountable

Space saving from compatible VESA mount standard (100 x 100 mm) and bundled ASUS miniPC kit(optional)



(By country)



Specification

Display	Panel Size(diagonal)	27" (68.58 cm) Wide Screen (16:9)
	Display Viewing Area(HxV)	596.74 x 335.66 mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	99% sRGB
	True Resolution	2560x1440
	Pixel Pitch	0.233 mm
	Brightness (Max.)	350cd/m ²
	Contrast Ratio	3000:1(Max); 1500:1 (Typical)
	Viewing Angle (CR \geq 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Refresh Rate	120Hz
	Response Time	5ms (GTG)
Features	Splendid™ Video Intelligence Tech.	Yes
	Color Temperature Selection	4 modes
	HDCP	Yes, 1.4
	QuickFit	Yes
	VRR Technology	Yes (Adaptive-Sync)
	PiP/PbP	Yes
	DisplayWidget	Yes, DisplayWidget Center
	ASUS Power Sync	Yes
Blue Light Filter	Yes	
Audio	Stereo Speaker	2W x 2 stereo, RMS
Input/ Output		USB-C (DP Alt mode with PD 96W), HDMI(v2.1) x 1 (TMDS), DisplayPort 1.4 x 2 (Daisy Chain), USB Hub (3x USB 3.2 Gen 1 Type-A+ 1x USB 3.2 Gen 1 Type-C), Earphone jack, RJ45
Power	Power Consumption	<18.15W ^{*1}
	Power Saving/Off Mode	<0.5W/ 0W(hard switch)
	Voltage	100-240V, 50 / 60 Hz
Mechanical Design	Chassis Colors	Black
	Tilt(angle)	+35° ~ -5°
	Swivel(angle)	+180° ~ -180°
	Pivot(angle/direction)	+90° ~ -90°
	Height Adjustment	0~150mm
VESA Wall Mounting	100x100mm	
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	61.22 x 52.78 x 22.4 cm (24.10" x 20.78" x 8.82")(highest with stand) 61.22 x 36.29 x 4.69 cm (24.10" x 14.29" x 1.85")(without stand)
	Box Dimension (WxHxD)	69.1 x 42.7 x 14.0 cm (27.20" x 16.81" x 5.51")
Weight		Net Weight : 7.0 kg (15.43 lbs) Net Weight without Stand : 5.0 kg (11.02 lbs) Gross Weight : 10.1 kg (22.27 lbs)
Accessories (vary by regions)		Power cord(1.8m), HDMI cable(1.8m), USB-C cable(1.5m), DisplayPort cable (optional), Warranty card, Quick Start Guide, MiniPC Kit (optional)
Compliance Standards		Energy Star, TCO, FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold(by country), TUV Flicker free, TUV Low Blue Light

*1.Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

*.All specifications are subject to change without notice.